



EAGLE HEAVY TEX

Textured coating containing hard aggregates and marble chips, based on modified acrylic emulsion, giving flexible finish with heavy texture for exterior and interior applications.

Product benefits

- Flexible, tough and weather resistant decorative texture coating.
- Excellent adhesion on interior/exterior surfaces.
- Protects surfaces as well as hides minor surface imperfections and hairline cracks.
- Good alkali resistance with anti fungal, anti bacterial properties.

Technical properties

Colour, dry film	Custom colors and factory-packed shade card colors
Finish, dry film	Matte / Heavy Texture
Volume solids	62 ± 2% (ASTM D2697)
Specific gravity	1.75 ± 0.02
Viscosity	Thixotropic paste
Spreading range	1.5 - 2.2 m ² / litre
Recommended dry film range	300 - 650 microns / coat (DFT)
Recommended wet film range	450 - 1000 microns / coat (WFT)
Flash point	Non Flammable

Product applications

- Eagle Heavy Tex is used as a heavy textured decorative coating for interior and exterior surfaces.
- Eagle Heavy Tex can be used to render on suitable substrates like concrete, plaster, prefabs, gypsum board, asbestos, brickwork, masonry work, etc.
- Eagle Heavy Tex is also suitable for application on wooden surfaces.
- Recommended for buildings, prefabs, boundary walls, etc.
- Additional protection and glossy finish can be obtained by over coating after full drying with Eagle Heavy Tex Polyurethane Topcoat, Eagle Acrylic Rock Topcoat or Eagle Gloss Emulsion.

Application data

Application method	Roller
Thinning / Cleaning	Water
Thinner (volume)	5 - 10 % depending on method of application

Recommended system

Eagle Acrylic Rock System	Prepared Surfaces	No. of Coats
To be applied on prepared surface.	Eagle Acrylic Primer	1 coat
	Eagle Heavy Tex	1 coat
	Eagle Heavy Tex Polyurethane Top Coat	1 or 2 coats *

* depends on surface properties

Drying time

Drying time @ 30°C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time)	
Touch dry	2 - 3 hours
Dry to recoat	6 - 8 hours
Hard dry	24 hours

Substrate preparation

Substrates should be sound, free of oil, grease, laitance and dust.

Loose particles, if any should be removed.

Make sure surface is free from fungal growth or other surface contaminants

A coat of suitable undercoat / primer as noted above is recommended for better adhesion.

Storage

Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shade, away from direct sunlight and extreme temperatures. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination.

Handle with care. Stir well before use.

Shelf life

12 months, in original sealed container, with proper storage conditions.

Packing / Colors

- 1 Litre tin
- 1 US gallon tin
- 5 US gallon drum
- All standard colors from shade card.
- Standard RAL colors.
- Customised special color options.

Safety and Health

Water base paints are generally quite safe to handle with due and diligent precautions.

As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Application must be carried out in well-ventilated area.

Local safety regulations to be followed.

Limited Guarantee : All Eagle Paints UAE LLC products are guaranteed for best performance; however since Eagle Paints UAE LLC does not control the final application of its products, nor the condition of the surfaces to which they are applied; a limited guarantee is provided. If the product does not perform as specified, Eagle Paints UAE LLC liability will under no circumstances exceed replacement of the product.

Disclaimer : To the best of our knowledge the information provided herein is true and accurate at the date of issuance. The company reserves the right to modify data contained herein without prior notice. Any change in data would normally be followed by issue of a new data sheet. The user should check with the nearest sales office of the company and confirm the validity of the information, prior to use of product.

Version No. EP / VN / 01 / 06 / 2018 Please note that this datasheet supersedes all previous versions.